

Salient Systems
10801 N Mopac Expy, Bldg 3, Ste 700
Austin, Texas 78759
512-617-4800
512-617-4801 FAX
www.salientsys.com

October, 2011

Product Guide Specification

Specifier Notes: This product guide specification is written according to the Construction Specifications Institute (CSI) 3-Part Format, based on *MasterFormat 2004* and *The Project Resource Manual—CSI Manual of Practice*. *The Manufacturer is responsible for technical accuracy. By removing the references to specific Salient Systems product names or part numbers, the text may also be used also in performance-based specifications.*

The section must be carefully reviewed and edited by the Architect or Engineer to meet the requirements of the project and local building code. *Italicized Words and sentences within brackets [] are choices to include or exclude a particular item or statement.* Coordinate this section with other specification sections and the Drawings.

Section 28 23 23 Video Surveillance Systems Infrastructure

PART 1 – GENERAL

1.1 SUMMARY

- A. Section Includes
 - 1. Video surveillance servers.
- B. Related Sections
 - 1. Section 28 23 13 – Video Surveillance Control and Management Systems.
 - 2. Section 28 23 16 – Video Surveillance Monitoring and Supervisory Interfaces.
 - 3. Section 28 23 19 – Digital Video Recorders and Analog Recording Devices.
 - 4. Section 28 23 29 – Video Surveillance Remote Devices and Sensors

1.2 REFERENCES

- A. Underwriters Laboratories, Inc. (UL) (www.ul.com)
 - 1. UL 50 Enclosures for Electrical Equipment.
 - 2. UL 60950-1 Information Technology Equipment - Safety.

1.3 SUBMITTALS

- A. Submit under provisions of Section [01 33 00].
- B. Product Data:
 - 1. Manufacturer's data, user and installation manuals for all equipment and software programs including computer equipment and other equipment required for a complete VMS.
- C. Shop Drawings
 - 1. System device locations on architectural floor plans.
 - 2. Full Schematic of system including wiring information for all devices.
- D. Closeout Submittals
 - 1. User Manuals
 - 2. Parts list.
 - 3. System device locations on architectural floor plans.
 - 4. Wiring and connection diagrams.
 - 5. Maintenance requirements.

1.4 QUALITY ASSURANCE

- A. Manufacturer shall have a minimum of 10 years experience in the manufacture and design of VMS products.
- B. Installer:
 - 1. Minimum of 5 years experience installing VMS products.
 - 2. All installation, configuration, setup, program and related work shall be performed by technicians thoroughly trained by the manufacturer in the installation and service of the equipment provided.

1.5 DELIVERY, STORAGE AND HANDLING

- A. Comply with requirements of Section [01 60 00].
- B. Deliver materials in manufacture's original, unopened, undamaged containers with original identification labels.
- C. Protect stored materials from environmental and temperature conditions following the manufacturer's instructions.
- D. Handle and operate products and systems according to manufacturer's instructions.

1.6 WARRANTY

- A. Provide manufacturer's warranty covering three (3) years for replacement and repair of defective equipment.

1.7 MAINTENANCE

- A. Make ordering of new equipment for expansions, replacements and spare parts available.
- B. Provide factory direct technical support to the installing firm.

PART 2 – PRODUCTS

2.1 VIDEO SERVER

- A. Manufacturer:
The Video Server shall be the RM1100 as supplied by:
Salient Systems Corporation
10801 N Mopac Expy, Bldg 3, Ste 700
Austin, Texas 78759
512-617-4800
512-617-4801 FAX
www.salientsys.com
- B. Substitutions:
Under the provisions of Division 1:
 - 1. All proposed substitutions must be approved by the Consultant or Architect/Engineer professional.
 - 2. Proposed substitutions must provide a line-by-line compliance document.

C. General Server Features:

1. The video server shall be integrated into a workstation-class computing platform ('PC'). The PC shall be available in a rack-mount chassis and shall fit in an EIA-standard 19" equipment rack utilizing no more than four units (4U) of rack space.
2. The server Operating System shall be Microsoft Windows 7 Professional.
3. Server shall have a lockable front panel.
4. Server shall be equipped with easily accessible front changeable air filter.
5. Server shall have front accessible USB ports.
6. Server shall have shock resistant disk drive bays.

D. Server System Components:

1. The server shall meet or exceed the following system component specifications:
 - a. Server shall utilize a Intel DP67BG motherboard
 - b. Server shall utilize Intel Core i5 Quad Core CPU \geq 3.0GHz
 - c. Server shall have at least 4GB of system memory
 - d. Server Storage Controller shall be 3Ware 9750—8i SATA/SAS 6Gb/s PCI express w/512MB Onboard Memory.
 - e. Server hard drives shall be Seagate Constellation ES SATA
 - f. Server shall provide between 2TB and 8TB of internal RAID5 storage for video event data.
 - g. Server shall have as the Network controller Gigabit (10/100/1000 Mbits/sec) LAN subsystem using Intel 82578DC Gigabit Ethernet Controller.
 - h. Server shall have Radeon HD 5450 512MB PCIe x16 Video Card
 - i. Server shall have 10 High-Speed USB 2.0 serial ports, for the attachment of external storage, digital I/O and archive devices.
 - j. Server shall have Line-level audio input, 1/8" stereo jack for digital capture of audio.
2. The server shall provide the following optional components:
 - a. Using analog frame grabber technology, the DVMS shall be capable of supporting between zero (0) and sixteen (16) NTSC, PAL, or SECAM, video sources, in increments of four (4) video sources.
 - b. Using digital video capture technology, the DVMS shall be capable of supporting between one (1) and fifty (50) IP-based video sources, in increments of one (1) video source.
 - c. If both analog frame grabber and digital video capture technologies are combined in the same PC, the cumulative total of video sources shall not exceed fifty (50), with no

- more than sixteen (16) of those sources being of the analog frame grabber type.
- d. For the capture of analog video sources, the DVMS shall utilize between one (1) and four (4) video frame grabber expansion boards that connect to the PC through either the Peripheral Connect Interface (PCI) bus or the Peripheral Connect Interface Express (PCIe) bus. The video frame grabber expansion board shall be available in two models, supporting the following standards:
 1. PCI revision 2.3
 2. PCIe x1
 3. The video frame grabber expansion board shall provide four (4) 75-ohms, auto-terminated BNC terminals for the connection of four (4) analog video sources.
 - e. The DVMS server shall support the following “Compression Formats” for analog video sources (NTSC, PAL, or SECAM):
 1. MJPEG
 2. MPEG4
 3. H.264
 - f. The video frame grabber expansion board shall utilize a separate video decoder for each video source, allowing for fully independent control of the following for each source:
 1. Brightness;
 2. Contrast;
 3. Hue;
 4. Saturation;
 5. Chroma.
 - g. Controlling software for the video frame grabber expansion boards shall utilize the Microsoft Windows Driver Model (WDM) architecture.
 - h. The server shall optionally provide support for between sixteen (16) and one-hundred (100) digital input and output points for wired integration with access control, building automation equipment, sensors, monitors, or other application requirements that may be determined at a later time. The server shall support any combination of the following digital input and output devices that are physically connected to the server via the PC’s USB bus:
 1. 8in + 8 out – 8 optically isolated digital inputs and 8 reed-relay outputs.
 2. 16 in – 16 optically isolated digital inputs.
 3. 16 out – 16 reed-relay outputs.
 4. 48 TTL – 48 TTL points defined as inputs or outputs in blocks of 8.

5. 96 TTL – 96 TTL points defined as inputs or outputs in blocks of 8.
3. The server shall support capture of video from cameras:
 - a. Server shall support any analog camera, NTSC or PAL, directly connected to optional analog frame grabber expansion board.
 - b. Server shall support IP cameras from leading camera manufacturers, with these video feeds connected through the server network controller without the need for encoders or other devices:
 1. ACTi
 2. American Dynamics
 3. Appro
 4. Arecont Vision
 5. Axis
 6. Basler
 7. Bosch
 8. Canon
 9. IQinVision
 10. Lumenera
 11. Panasonic
 12. Pelco
 13. Samsung
 14. SmarterCam
 15. Sony
 16. Toshiba
 - c. Server shall support control of PTZ camera (analog or IP) from leading camera manufacturers:
 1. ACTi
 2. American Dynamics ASCII
 3. Axis
 4. Bosch
 5. Canon VCC-4
 6. Kalatel
 7. Panasonic: conventional and new (analog)
 8. Panasonic IP
 9. Pelco: ASCII, D, P (analog)
 10. Pelco IP
 11. Philips BiPhase
 12. RVision
 13. SAE
 14. Samsung
 15. Sensormatic
 16. Sony EVI –D30/D31
 17. Sony P5 IP
 18. Sony Visca IP

- 19. Toshiba IK-WB IP
- 20. Toshiba IK-WB21A IP
- 21. Ultrak
- 22. VCL
- 23. Vicon

E. Chassis Features:

- 1. The Form Factor shall be 4U.
- 2. The dimensions shall be 20.5" x 16.9" x 6.9"
- 3. Front ports shall be 2x USB.
- 4. Cooling shall be 1x 120mm and 1x 80mm Internal Fans

F. Electrical:

- 1. Input Voltage: AC 100-240V 50/60Hz.
- 2. Power Supply: 620W AC-DC, 80 PLUS Certified

G. Environmental:

- 1. Temperature Range:
 - a. Operating: 50 to 95 degrees F (10 to 35 degrees C)
 - b. Non-Operating: 22 to 140 degrees F (-5 to 60 C)
- 2. Relative Humidity Range:
 - a. Operating 10 – 90% (non condensing at ambient)
 - b. Non-operating 5-95% (non-condensing at ambient)

PART 3 – EXECUTION

3.1 EXAMINATION

- A. Examine area to receive devices and notify any adverse conditions affecting installation or subsequent operation.
- B. Do not begin installation until unacceptable conditions are corrected.

3.2 PREPARATION

- A. Protect devices from damage during construction.

3.3 INSTALLATION

- A. Install devices in accordance with manufacturer's instruction at locations indicated on the floor drawing plans.
- B. Perform installation with qualified service personnel.

- C. Install devices in accordance with the National Electrical Code or applicable local codes.
- C. Ensure selected location is secure and offers protection from accidental damage.

3.4 FIELD QUALITY CONTROL

- A. Test snugness of mounting screws of all installed equipment.
- B. Test proper operation of all VMS devices.
- C. Determine and report all problems to the manufacturer's customer service department.

3.5 ADJUSTING

- A. Make proper adjustment to video system devices for correct operation in accordance with manufacturer's instructions.

3.6 DEMONSTRATION

- A. Demonstrate at final inspection that the VMS is functioning properly.

END OF SECTION