

## Enterprise Level

# POWERPLUS

Salient's PowerPlus is a 2U rack-mount NVR offering an excellent balance between processing power, storage capacity, redundancy for high performance and a flexible platform for video surveillance applications. The PowerPlus incorporates a RAID for its operating system. Power-built for the rigors of continuous duty operation using advanced components, the 2U rack-mountable PowerPlus NVR delivers the reliability and processing power required for mission critical video surveillance.

Lower overall system-level power draw is the result of breakthrough system design. The PowerPlus NVR maximizes performance per watt through a combination of power and cooling, and energy efficient technologies and tools.

## FEATURES

- Record, live view, playback, archive video
- Front access with locking bezel for hot swap
- Rack mount 2U form factor
- Front access with locking bezel for hotswap



# POWERPLUS

## SYSTEM SPECS

Operating System	Windows Server 2019 Standard Embedded	Graphics Adapter	Integrated
Processor	Single Intel Xeon	Max Resolution	1920x1200
Memory	32GB	Video Display Ports	1 VGA (front), 1 VGA (rear)
Network	Quad 1Gbe NICs	USB Ports	2 USB 2.0 (front), 1 USB 3.0 (front), 2 USB 3.0 (rear)
Hard Drive (OS)	2 - 1TB in RAID 1 configuration	Other Ports	1 serial port (rear)
Hard Drive (Video Storage)	Up to 60TB	PCIe Slots	1x FHFL x16, 1x FHFL x8, 1x FHHL x8, 1x LPHL x8
RAID Controller	Yes	Optical Drive	Optional external USB attached DVD-RW
RAID Level of Storage	5 or 6 (When supporting RAID 6, one PCIe slot will be consumed)	Accessories	Keyboard, mouse & rail kit included
# of Hot Spares Supported	1	TPM Support	Yes
		Life Cycle Controller	iDRAC 9
		Life Cycle Controller Software	ACIA - iDRAC Enterprise software license for PowerUltra or PowerPlus with iDRAC V9
		DAS Support	Yes - PERC RAID controller required. Part number ACDB. Requires 1 PCI-E slot

## CHASSIS FEATURES

Form Factor	2RU Rackmount
Height	3.42 inches (86.8 mm)
Width	18.98 inches (482.0 mm)
Depth	28.17 inches (715.5 mm)
Weight	63.05 lbs (28.6kg)

## WARRANTY

3 and 5 year (basic, NBD, or 4HR)

Company and product names mentioned are registered trademarks of their respective owners. Salient Systems reserves the right to change specifications without prior notice. Copyright Salient Systems. 8/2022

## OPERATING ENVIRONMENT

Operating Temp.	50°F - 95°F (10°C - 35°C)
Power Supply	Dual 1100W - 100 to 240VAC auto ranging and redundant
Relative Humidity	
Operating:	10% - 80% non-condensing Max dew point 84.2°F
Storage:	5% - 95% non-condensing Max dew point 91°F
BTU	4100 BTU/hr

